
WALL LIGHT (

Cleaning

Warning: Before cleaning, disconnect from mains supply and allow luminaire to cool.





Disposal

Ensure correct disposal of this product (waste electrical and electronic equipment).



It is important to note that care must be taken during installation or maintenance to ensure that the surface of the luminaire is not damaged. Any damage, which is exposed to moisture will result in corrosion occurring.

Please also note that any chemical applications on the luminaire or chemical contact via installation will cause corrosion of the surface of the luminaire and will void the warranty.

Ambient Conditions

Recommended to install in an ambient temperature <35°C.





Link

Luminaire

LINKO255

Grill face LIGRO255

Open face LIOP0255 Power 10 Watts

Codes

Base

Class III 24V DC **IP Rating** 65

Material

Install Person/s







CAUTION - This product must be installed by a qualified installer

Please read instruction manual carefully before installing luminaire




Surge Protection


For comprehensive protection of a luminaire against electrical surges, surge protection shall be installed on the mains supply where required to protect luminaires and drivers from transient voltage damage.

For warranty information visit unios.com/warranty

Please read these installation instructions carefully before installing this product. This product must be installed and maintained by a suitably qualified person/s in compliance with the latest applicable regulations and relevant legislation.

Unios does not warrant any claim based on defects or damage caused by misuse, improper installation, improper operation and/or modifications carried out by the purchaser or third parties. This product shall not be used as a 'working light' during construction. This will result in the warranty of the product to be void. For warranty duration, please refer to the data sheet.





Sizing Variations

Luminaire

Product Code	Α	В	С
LINKO255	255	75	48
Wallbox			
LINKO255	250	70	82

All measurements are in millimetres.

Parts




















Wiring





IP Connection



Driver Selection

Product Code	Output Power	Forward Voltage
LINKO255	10W	24V DC

Dimming

For dimming capabilities, luminaire must be paired with dimmable driver. Please refer to driver's instructions for pairing of suitable systems.

